

White Light - 2400mm

Description:

A 100% blackout fabric suitable for Roller and Panel Blinds. 10 colourways, all with pearlescent solar reflective coating, giving high solar energy performance. Uniform appearance from outside. Ideal for strata management, public buildings etc. Advanced Flame Retardancy meeting European and US standards. The PVC free acrylic coating has anti-fade, easy clean and antifungal properties.

Key Features:

- Width: 2400mm
- Suitable for: Roller & Panel Blinds
- Colourways: 10
- Quality: Blackout
- Characteristics: Dust & Mould Resistant, Fade Resistant, Easy Care, PVC Free, X-Link Technology

Specification: Blackout (1WHL)

- Composition: 100% Polyester with Acrylic Coating. Pearlescent backing
- Weave: Plain Weave
- Flame Retardant:
 - Tested to AS 1530 Part II & Part III
 - BS 5867 Part II, Type B
 - NFPA 701 TM#1 Small Scale
 - California US Title 19 (small scale)
- Light Fastness: 6 minimum
- Nominal Thickness: 0.30mm
- Nominal Weight: 380gsm
- Cutting: Ultrasonic, cold, crush, knife

Solar Optical Properties

Generic Timber Window Frame				
Ts	Rs	As	Tv	U-Value w
0	0.647	0.353	0	3.8

Manufactured:

Australia

Care:

Fabric should be regularly dusted/vacuumed. Remove marks by sponging gently with mild detergent in luke warm water. If commercial spot cleaner is used, first test in an inconspicuous area.

Warranty: 2 years, Lifetime anti-fade guarantee

Colour Range *



White Light



* colours representative only